

General Information

Company Name & Address	KHALID FARAJ SHIPPING PO BOX 995, ABU DHABI, U.A.E.
Flag	U.A.E.
Year of Built	2006
Official No.	5333
Call sign	A6E3067
MMSI	470906000
IMO No	9418676
Classification	Bureau Veritas
Class Notation	Hull. Mach. Deck Ship/ Cargo Ship
Place of Build	Malaysia
Vessel Contact No.	+971506162074
Head Office No & Fax:	+971 2 6984999 +971 2 6659218
Vessel e mail	lct.taibah@gmail.com
Company E-mail	commercial@khalidfarajshipping.com
Company website	www.khalidfarajshipping.com


Vessel Built Specs / Principle Dimensions

LOA, Length Overall	64.00 Meters	Light Ship	621.359 TONNES
LBP	60.302 Meters	GRT	869
BEAM Moulded	14.00 Meters	NRT	260
Depth Moulded	3.65 Meters	DWT	1210.112 Tons
Draft (Summer)	2.70 Meters	Summer Displacement	758.529 MT
Air Draft	18.95 Meters	Light Ship Draft	1.847 Meters

Vessel Performance Particulars

Max Speed	10 Knots (Free running)	Fresh Water Consumption	1.5 MT
Economical Speed	07 Knots	Fuel Type	MGO
Fuel Consumption at max speed	160 ltr/ hr	Fuel Consumption at Economical speed	126 ltr/hr

Vessel Cargo Particulars

Clear Deck Space Area	576 m ²	Deck Strength	7 T/M ²
Cargo Tank Details	F.O- 08 TANKS F.W-02 TANKS	Maximum Height Of Cargo Allowed	02 METERS
Total Cargo Weight The Vessel Can Carry/DWCC	1210.112 MT	No Of Refer Sockets	4
Cargo Doors/Ramp Doors Details	7.00m X 8.25m	Clean deck dimension, L * B in M	40,2M x 12M

Vessel Capacities

Fuel Tanks	375 m ³	Fresh Water Tanks	21 m ³
------------	--------------------	-------------------	-------------------

Accommodation Details (SPLIT TYPE AC EACH CABIN)

No Of Crew Berths	10	No Of Passenger Berths	-
-------------------	----	------------------------	---

Propulsion And Machinery Details

Main Engines	2 x 640 BHP Cummins KTA19-M3,	Generator	2 x 91.0KW Cummins 6BT5.9D(M)
Gear Box	TWIN DISC, MG-5222	Propulsion	FIXED PITCH PROPULSION
Bow Thruster	NOT APPLICABLE	Emergency Generator	CUMMINS ES55D5 50KW@1500r/min
Gear Box	NOT APPLICABLE	Ballast Water Treatment system	
Sewage Tank	NOT APPLICABLE	Sewage Treatment System	ISS-15

Communication And Navigation Equipment

VHF	FURUNO 1C-317/ SAMYUNG STR-6000A	NAVTEX	FURUNO NX-700
SSB	FURUNO IC-3150	Magnetic Compass	MDL SR 150 PK
Radar	FURUNO RPU-0111	AIS	FURUNO FA-150
GPS	FURUNO GP-150/ GP-39	Auto Pilot	SIMRAD AP-50
Echo Sounder	FURUNO TYPE FE-700	GYRO COMPASS	SIMRAD GC80/GC85
INMARSAT	FURUNO IC-306	ECDIS	

LSA And FFA Equipment

Navigation & Search Light	AVAILABLE	2 x 16 men Inflatable Life Raft	16FK+
Fire Fighting as per SOLAS	AVAILABLE	Rescue Boat	SC-45KR

Special Features Details

FiFi pump details		Spray Boom Details	
Oil Spill & Recovery Equ't Details	SOPEP BOX	Rescue Boat	SC-45KR
Main ballast water management method(s) used on the ship		Deepest ballast drafts (Normal & Heavy Weather)	2.7 METER
Total ballast capacity of the ship in cubic meters.	1 767.6 m ³	Identification (rank) of the appointed ballast water management officer	Chief Officer